





TECHNICAL SPECIFICATIONS

Screw caps DIN 51



		Article name	Article number	Color*
	Screw cap with retaining ring	VS DIN 51-PE/G SR	6916	black
		VS DIN 51-PE/G SR	6824	white
	Pull-out cap with locking ring	VS DIN 51-PE/G SR	6409	black
	Lid tap with ventilation	VS DIN-51-PE/G AH 23	6822	black

*various colors available upon request

MATERIAL

- Base material polyethylene (HDPE)
- Masterbatch
- All materials used have been approved in accordance with food legislations

APPLICATIONS

- Flavors and fragrances
- Cleaning agents
- Disinfectants
- Foods (fatty, acidic, aqueous, alcoholic)
- Active pharmaceutical ingredients

ENVIRONMENT

- HDPE harmlessly destructible
- Dyes are free of heavy metals

PRODUCTION / QUALITY ASSURANCE

- ISO 9001 certified
- BRC production
- Low-germ filtered blown air
- Controlled production (particles, microbiology, migration)
- Hygiene standards

SUITABLE FOR

- Canister type K6 - 5, 6, 10 and 12 liter

TIGHTENING TORQUE

- 8 - 12 Nm

APPROVAL

- Food packaging in accordance with EC 1935:2004
- 2002/72/EG
- Consumer goods ordinance
- UN recommendations on the Transport of Dangerous Goods according to ADR/SDR, RID/RSD, IATA
- Declaration of conformity according to EU/10/2011

STORAGE STABILITY (WITHOUT FILLING MATERIAL)

- When stored correctly (dry, out of sunlight and at temperatures between 5° and 30° C), the product can be kept for up to two years after the production date.